

DVS-005 Series

Unmanaged Industrial 5-Port FE Ethernet Switches



- ▶ 12 to 48 VDC redundant terminal block power input
- ▶ Auto warning by relay output for link-down and power failure
- ▶ Compatible with various industrial protocols, including EtherNet/IP, Profinet, EtherCAT, CC-LINK IE, and DNP 3.0

Specification

TECHNOLOGY

Standard Compliance

- IEEE 802.3 10Base-T
- IEEE 802.3u 100Base-T(X) and 100Base-FX
- IEEE 802.3x Flow Control

Processing Type

- Store and forward
- IEEE 802.3x flow control in full duplex, back-pressure flow control in half duplex

INTERFACE

Fast Ethernet

RJ45 Ports:

- 10/100Base-T(X), auto MDI/MDI-X, auto negotiation

Fiber Optic Ports:

- 100Base-FX (SC connector), MultiMode or SingleMode

LEDs

Per Device:

- ALARM, PWR1, PWR2

Per Port:

- 100M (RJ45 port), 100M (fiber port), LINK/ACT

DIP Switches

Port link-down alarm configuration

Alarm Contacts (DO)

- 1 relay output
- Carry current 5A@24VDC

PERFORMANCE AND SCALABILITY

Switching Capacity

- 1Gbps, wire-speed, non-blocking switching fabric

Forwarding Rate

- 1.5Mpps

MAC Address Table

- 1K

Packet Buffer Memory

- 512M bits

POWER REQUIREMENTS

Input Voltage

DVS-005W series:

- 2 sets, 12 to 48 VDC redundant terminal block power input

DVS-005100:

- 1 set, 12 to 48 VDC terminal block input

Input Current

- Max. 0.24A

Overload Current Protection

- Present, max. input current 3A

Reverse Polarity Protection

- Present

Buffer Time

- Min. 13ms at 24VDC

PHYSICAL

Housing

- IP40 aluminum metal case

Dimensions

- 145.3mm (H) x 45mm (W) x 108.7mm (D)

Weight

- 300g

Installation

- Industrial DIN-Rail and wall mounting

Specification

ENVIRONMENTAL LIMITS

Operating Temperature

DVS-005W series:

- -40°C to 75°C (-40°F to 167°F)

DVS-005I00:

- -10°C to 60°C (14°F to 140°F)
- Tested @ -25°C to 70°C (-13°F to 158°F)

Storage Temperature

- -40°C to 85°C (-40°F to 185°F)

Ambient Relative Humidity

- 5% to 95% (non-condensing)

APPROVALS

Safety

- UL 508, EN 60950-1, IEC 61131-2

EMI

- FCC 47 CFR Part 15 Subpart B Class B, IEC 61000-6-4, EN 55022

EMS (IEC 61000-6-2)

- IEC 61000-4-2 level 3, IEC 61000-4-3 level 3, IEC 61000-4-4 level 4, IEC 61000-4-5 level 3, IEC 61000-4-6 level 3, IEC 61000-4-8 level 4, IEC 61000-4-29

Environmental Type Tests

Cold Temperature:

- IEC 60068-2-1

Dry Heat:

- IEC 60068-2-2

Humidity:

- IEC 60068-2-30

Shock:

- IEC 60255-21-2

Freefall:

- IEC 60068-2-32

Vibration:

- IEC 60068-2-6

Hi-Pot:

- 1.5KV

Fiber optics

	100Base-FX	
	MultiMode	SingleMode
Cable	62.5/125µm, 50/125µm	9/125µm
Wavelength	1310nm	1310nm
Max. TX Power	-14dBm	-8dBm
Min. TX Power	-20dBm(1) -22.5dBm(2)	-15dBm
RX Sensitivity	-31dBm	-31dBm
Optical Budget	11dBm(1) 8.5dBm(2)	16dBm
Max. Link Distance	5km	30km

(1) 62.5/125µm fiber optic cable (2) 50/125µm fiber optic cable

Note: The actual link distance of a particular fiber optic link depends on the optical budget, the number of connectors and splices, and cabling quantity. Please measure and verify the actual link loss values once the link is established to identify any potential performance issues.

Ordering Information

Product		Port Combination			Interface		
Model Name	Operating Temperature	10/100 Base-T(X)	100Base-FX		DI	DO (Relay)	Power Input
			SC Connector, MultiMode, 5km	SC Connector, SingleMode, 30km			
DVS-005I00	-10°C to 60°C	5	---	---	---	---	1
DVS-005W01	-40°C to 75°C	5	---	---	---	1	2
DVS-005W01-MC01	-40°C to 75°C	4	1	---	---	1	2
DVS-005W01-SC01	-40°C to 75°C	4	---	1	---	1	2

Optional Products

DVP/CliQ/PMC Series: 12/24 VDC Industrial Power Supply